



### Features & Benefits:

- IP68 rating: ideal for use in dry or damp locations
- Low input voltage and power consumption
- Weather resistant design
- Wide viewing angle - 160°
- Dimmable
- 5-year warranty

### Population Guide:

<b>Channel Depth:</b>	3-6" [7.5-15 cm]
<b>Stroke Width:</b>	4" [10 cm]
<b>Modules per Foot:</b>	2
<b>Modules per Meter:</b>	6

### Notes:

1. L70 Lifetime: 50,000 Hours.
2. To avoid voltage drop, the following guideline of installation is recommended:  
Max. 50 modules per run @ wire gauge: 20AWG.

### Technical & Optical Data:

<b>Input Voltage:</b>	12V DC
<b>Working Current:</b>	60 mA
<b>LED Color:</b>	White/Neutral White /Warm White
<b>Color Temperature:</b>	6500K/4000K/3000K
<b>Viewing Angle:</b>	160°
<b>LED per Unit:</b>	3
<b>Wattage per Unit:</b>	0.72 W
<b>Light Output per Unit:</b>	75 Lm
<b>Lumen per Foot [Meter]:</b>	150 Lm [480 Lm]
<b>Luminous Efficacy:</b>	100 Lm/W
<b>Operating Temp.:</b>	-40 to 185°F [-40 to 85°C]

**CE** **cUL<sup>®</sup>US** **IP68** **RoHS**

### Dimensions:

